Orka

LED | A | A+ | A++ | 90° | 350° | SASO | CB | LVD | CE | EAC | F | IP20

CRI 90 | CRI 98

5 / Product Color / Ürün Renk

WHITE = 01 | Ral 9010 = 02 | BLACK = 03 | GRAY = 04 | DARK GRAY = 05 | SPECIAL COLOR = 06

4 / Reflector Angle / Reflektör Açısı



Technical Drawing / Teknik Çizim



- Die-cast aluminium body.
- Mains voltege: 220-240V / 50-60Hz.
- Clever thermal design with passive heat dissipation.
- Deep recessed light source for low glare visual comfort.
- Precision optical control.
- 90° tilt adjustment and 350° rotation.
- CRI90 / 98 options with CCT range 2700K - 5000K.
- Classic dimming systems of DALI, 1-10V and Phase-Cut Dim options.
- High tech control systems of Tuneable White, Warm Dim and Wireless Dim options.
- Basic colours: White, Black, Gray, Dark Gray, RAL9010 and special color options.
- Honeycomb filter can be added.
- Super Spot, Spot, Medium, Flood and Wide Flood beam angle options available: 9° / 18° / 24° / 36° / 50°.
- High efficiency LED module up to 2100+lm.
- Standart CRI>80, high CRI>90 and super high CRI>98 LED options available.
- High colour consistency: <3 SDCM

Orka / I01.MLT.60832

Power / Güç	CRI	Order Code / Sipariş Kodu	Kelvin	Lümen T_C=50° Lümen
24W	CRI>90	I01.MLT.60832 . (..) . (...) . (..) . (..)	2700K	2058
			3000K	2100
			3500K	2142
			4000K	2185
	CRI>98	I01.MLT.60832 . (..) . (...) . (..) . (..)	2700K	1545
			3000K	1575
			3500K	1610
			4000K	1640

* Code example / Kod örneği:

I01.MLT.60832 . 24 . 827 . SP . 01

1 2 3 4 5

(..) / Complete Code / Komple Kod

2	Watt - Driving Current / Watt - Sürüş Akımı
24	24W - 600mA
21	21W - 500mA

3	CRI / Kelvin		
927	CRI>90 - 2700K	9835	CRI>98 -3500K
930	CRI>90 - 3000K	9840	CRI>98 -4000K
935	CRI>90 - 3500K		
940	CRI>90 - 4000K		
9827	CRI>98 - 2700K		
9830	CRI>98 - 3000K		

4	Reflector Angle / Reflektör Açısı
SS	9° - Super Spot
SP	18° - Spot
ME	24° - Medium
FL	36° - Flood
WF	50° - Wide Flood

5	Product Color / Ürün Renk
01	white
02	ral 9010
03	black
04	gray
05	dark gray
06	special color