

Lite Recessed

Key advantages

- Slim rectangular and round recessed luminaire for outdoor installation on wall.
- Installation: Luminaire is supplied with plastic outer installation box for easy mounting.
- The body is protected by a special antioxidizing treatment for a higher resistance against aggressive agents. Salt spray test being applied to ensure stability of finishing.
- The heat generated by the light source is dissipated by means of a passive cooling system.
- The luminaire is equipped with a piece of cable for mains to provide easy-to-make connection.

EN

- Corrosion resistant die-cast aluminium body.
- Mains voltage: 220-240V / 50-60Hz.
- Clever thermal design with internal cooling pins.
- Led colour temperatures are optionally 2700K, 3000K, 3500K, 4000K, 5000K and 6500K.
- Internal silicon gaskets ensure IP protection.
- All external screws are stainless steel.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- High colour consistency: <3 SDCM
- L80 B10 50000hrs and five years warranty.

Kilit Avantajları

- Slim dikdörtgen ve yuvarlak forma sahip ankastre duvara monte armatür serisi.
- Montaj: Kolay montaj için armatür plastik dış alçı kasaya sahiptir.
- Gövde boyası oksitlenmeye karşı özel korumalıdır. Armatürler tuz testi ile oksitlenmeye karşı koruma tip testine tabi tutulmaktadır.
- Pasif soğutucu sistemine sahiptir.
- Armatür 220V enerji girişi kablosu üzerinde verilmektedir. Enerji bağlantısı için armatürü açmaya gerek yoktur.

TR

- Korozyona dayanıklı alüminyum enjeksiyon gövde.
- 220-240V / 50-60Hz enerji girişi.
- 2700K, 3000K, 3500K, 4000K, 5000K ve 6500K renk sıcaklığı seçenekleri mevcuttur.
- Silikon contalar ile IP koruması sorunsuz sağlanır.
- Tüm dış vidalar paslanmazdır.
- Çift katmanlı polyester toz boya sayesinde korozyona ve tuza dayanıklı.
- Yüksek renk uyumu: <3 SDCM
- L80 B10 50000 saat ve beş yıl garanti.

Lite Recessed



5 / Product Color / Ürün Renk



White = 01



Light Gray = 04




Textured Metallic
Dark Gray = 05





Black = 03

Lite Recessed / O07.WA.00020



| Power / Güç | CRI | Order Code / Sipariş Kodu | Kelvin | Lümen T _c =50° Lümen |
|-------------|--------|---|--------|------------------------------------|
| 4.5W | CRI>80 | O07.WL.00020 . (..) . (...) . (..) . (..) | 2700K | 132 |
| | | | 3000K | 135 |
| | | | 3500K | 141 |
| | | | 4000K | 146 |
| | | | 5000K | 148 |
| | | | 6500K | 152 |



* Code example / Kod örneği:



O07.WA.00020 . 5 . 827 . ASM . 01

1 2 3 4 5

Lite Recessed / O07.WA.00021



| Power / Güç | CRI | Order Code / Sipariş Kodu | Kelvin | Lümen T _c =50° Lümen |
|-------------|--------|---|--------|------------------------------------|
| 4.5W | CRI>80 | O07.WL.00021 . (..) . (...) . (..) . (..) | 2700K | 161 |
| | | | 3000K | 164 |
| | | | 3500K | 171 |
| | | | 4000K | 176 |
| | | | 5000K | 178 |
| | | | 6500K | 183 |



* Code example / Kod örneği:

O07.WA.00021 . 5 . 827 . ASM . 01

1 2 3 4 5

| 2 | Watt / Watt | | 3 | CRI / Kelvin | | 4 | Reflector Angle / Reflektör Açısı | | 5 | Product Color / Ürün Renk | |
|---|-------------|------|-----|----------------|----------------|---|-----------------------------------|------------|---------------|---------------------------|-------|
| | 5 | 4.5W | | 827 | CRI>80 - 2700K | | ASM | Asymmetric | | 01 | white |
| | | | 830 | CRI>80 - 3000K | | | | 02 | ral 9010 | | |
| | | | 835 | CRI>80 - 3500K | | | | 03 | black | | |
| | | | 840 | CRI>80 - 4000K | | | | 04 | gray | | |
| | | | 850 | CRI>80 - 5000K | | | | 05 | dark gray | | |
| | | | 865 | CRI>80 - 6500K | | | | 06 | special color | | |

(..) / Complete Code / Komple Kod