





5 / Product Color / Ürün Renk



4 / Reflector Angle / Reflektör Açısı



Technical Drawing / Teknik Çizim



- Die-cast aluminium body.
- Mains voltage: 220-240V / 50-60Hz.
- Clever thermal design with passive heat dissipation.
- Deep recessed light source for low glare visual comfort.
- Precision optical control.
- 90° tilt adjustment and 350° rotation.
- CRI90 / 98 options with CCT range 2700K - 5000K.
- Classic dimming systems of DALI, 1-10V and Phase-Cut Dim options.
- High tech control systems of Tuneable White, Warm Dim and Wireless Dim options.
- Basic colours: White, Black, Gray, Dark Gray, RAL9010 and special color options.
- Honeycomb filter can be added.
- Super Spot, Spot, Medium, Flood and Wide Flood beam angle options available: 9° / 18° / 24° / 36° / 50°.
- High efficiency LED module up to 2100+lm.
- Standart CRI>80, high CRI>90 and super high CRI>98 LED options available.
- High colour consistency: <3 SDCM

Orka / I01.MLT.60831

	Power / Güç	CRI	Order Code / Sipariş Kodu	Kelvin	Lümen T _c =50° Lümen
	24W	CRI>90	I01.MLT.60831 . (..) . (...) . (..) . (..)	2700K	2058
				3000K	2100
				3500K	2142
				4000K	2185
		CRI>98	I01.MLT.60831 . (..) . (...) . (..) . (..)	2700K	1545
				3000K	1575
				3500K	1610
				4000K	1640

* Code example / Kod örneği:

I01.MLT.60831 . 24 . 827 . SP . 01

1 2 3 4 5

2	Watt - Driving Current / Watt - Sürüş Akımı		3		CRI / Kelvin		4	Reflector Angle / Reflektör Açısı		5	Product Color / Ürün Renk			
	24	24W - 600mA	927	CRI>90 - 2700K	9835	CRI>98 -3500K			SS		9° - Super Spot		01	white
	21	21W - 500mA	930	CRI>90 - 3000K	9840	CRI>98 -4000K			SP		18° - Spot		02	ral 9010
			935	CRI>90 - 3500K					ME		24° - Medium		03	black
			940	CRI>90 - 4000K					FL		36° - Flood		04	gray
			9827	CRI>98 - 2700K					WF		50° - Wide Flood		05	dark gray
			9830	CRI>98 - 3000K									06	special color