




Geo Aplique



Geo Aplique / O07.WA.00078

Code / Kod	WA.00078	
System Power / Sistem Gücü	20W	
Lumen Output from Fixture / Armatür Çıkış Lümeni CRI>80	2700K	1975
	3000K	2015
	3500K	2055
	4000K	2100
	5000K	2160
Driving Current / Sürüş Akımı	500mA	
Dali Dimming Option / Dali Dim Seçeneği	✓	
1-10V Dimming Option / 1-10V Dim Seçeneği	✓	



EN

- Corrosion resistant die cast aluminium alloy.
- Installation with bracket on walls.
- Mains voltage: 220-240V / 50-60Hz.
- Symmetric light distribution to three direction through windows.
- Led colour temperatures are optionally 2700K, 3000K, 3500K, 4000K and 5000K.
- PC Diffuser.
- Weatherproof and durable silicone rubber gasket.
- Ultraviolet stabilized polyester powder coat finish in white, black, dark grey and light gray finish.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- All external screws are stainless steel.
- High colour consistency: <3 SDCM

TR

- Korozyona dayanıklı alüminyum gövde.
- Duvara braketli montaj sistemine sahiptir.
- 220-240V / 50-60Hz enerji girişi.
- Armatür üzerindeki pencerelerden üç yöne simetrik ışık çıkışı.
- 2700K, 3000K, 3500K, 4000K ve 5000K renk sıcaklığı seçenekleri mevcuttur.
- Polikarbon diffüzörlü.
- Su geçirmezliği sağlayan silikon conta.
- Ultraviyole ışımaya dayanıklı beyaz, açık gri, antrasit gri ve siyah elektrostatik toz boyalı.
- Çift katmanlı polyester toz boya sayesinde korozyona ve tuzla dayanıklı gövde.
- Tüm dış civatalar paslanmaz çelik.
- Yüksek LED renk uyumu: <3 SDCM